

PASSIONATE ABOUT INNOVATION

MEDICAL

orthodrive® lite

www.de-soutter.com



LITE ON COST • LITE ON WEIGHT • LITE ON VIBRATION • BIG ON POWER

DOES MORE, FOR LONGER, WITH BETTER PERFORMANCE

LITE HANDPIECE

- We are pleased to introduce our elegant straight case modular handpiece with its unique dual position trigger function, allowing complete grip flexibility.
- Lightest large bone system on the market delivering unmatched power to weight performance.
- Continuous development in handpiece ergonomics ensures class leading surgeon comfort.
- Effortless attachment assembly. Simply 'push and click' and you are ready to go.



INNOVATIVE SAW HEAD DESIGN

- Innovative 'Zero Play' blade mounting mechanism eliminates unwanted vibration and noise.
- Superior saw head reliability is achieved through the reduction of mechanical play within the saw mechanism.
- Simple blade loading is achieved with a totally unique 'push and click' action.



TOTAL SYSTEM FLEXIBILITY

- Complete compatibility with existing De Soutter Medical systems already on site, ensuring cost containment.
- The orthodrive® Lite system provides greater flexibility than ever before allowing it to be used for both large bone and trauma procedures, without compromising performance.





ORTHODRIVE LITE SYSTEM

DEDICATED ATTACHMENTS

DRILLING	Order code	Model	Description	Speed rpm	Cannulation Ø mm
	17600	DQ-708	0.5 - 7.4 mm (1/4")	0 - 1350	4.4
	17610	DQ-708	Small A.O. Synthes/ASIF	0 - 1350	2.1
QUICK RELEASE RE	AMING				
	17620 17630 17840	RQ-708 RQ-708 RQ-708	Large A.O. Synthes/Protec Hudson/Zimmer combi Hudson	0 - 330 0 - 330 0 - 330	4.4 4.4 4.4
HIGH SPEED BUR	17850	RQ-708	Zimmer	0 - 330	4.4
	19890 19880 19870	BQ-707 BQ-707 BQ-707 Uses R60	Bur - standard (72mm) Bur - long (197mm) Bur - extra long (273mm) -5XX series rotary burs	0 - 20000 0 - 20000 0 - 20000	- - -
SAWING					
	17640	KQ-707	Large sagittal saw Uses S89 type blades	0 - 13500	cpm -
	17680	NQ-707	Small sagittal saw Uses S88 type blades	0 - 20000	cpm -
	17660	CQ-707	Reciprocating saw Uses S84 type blades	0 - 13500	cpm -
WIRE AND PIN DRIV	/ER				
	17700 18240 18220 18230	WQ-707 WQ-708 PQ-707 PQ-708	0.7 - 4.0 mm wire capacity 0.6 - 2.0 mm wire capacity 1.8 - 3.2 mm pin capacity 2.6 - 4.0 mm pin capacity	0 - 1350 0 - 1350 0 - 1350 0 - 1350	4.0 4.0 4.0 4.0
ATTACHMENTS FOR	USE WIT	H FINAL	DRIVE ADAPTORS		
	17570	GQ-707	Drill/reamer	0-330/0- 1200	4.4
	17590	RQ-707	Reamer	0 - 330	4.4
	17580	DQ-707	Drill	0 - 1350	4.4
RADIOLUCENT ATT	ACHMENT				
	17690	TQ-707	Accepts radiolucent drill final drive	0 - 1350	-
CIFICATION			arthodorius 🖉 🔊 📄		

HANDPIECE SPECIFICATION

Model	Order code	Description	Drilling speed	Maximum reaming torque	Cannulation Ø mm	III II
MBQ-707	1289334	Single trigger	0 - 1350 rpm	16 Nm	4.4	
MBQ-708	1289444	Dual trigger	0 - 1350 rpm	16 Nm	4.4	
MBQ-807	1293554	Straight case	0 - 1350 rpm	15 Nm	4.4	orthodriei dar

See pages 6 - 8 for range of aseptic and sterile battery systems.

DRILLING	Order code	Description	Cannulatior Ø mm
	15360	0.5 - 4.0 mm (5/32") keyed	3.1
	15370	0.5 - 7.4 mm (1/4") keyed	4.2
	15380	0 - 3.0 mm (1/8") keyless	3.0
	15390	0.3 - 7.4 mm (1/4") keyless	4.2

FINAL DRIVE ADAPTORS - Final drive speeds are as drive attachment selected

QUICK RELEASE DRILLING AND REAMING

	15480	Small A.O. Synthes/ASIF	2.5
	15490	Large A.O. Synthes/Protec	4.2
	15530	Hudson	4.2
	15540	Trinkle	4.2
-36	15460	Zimmer	4.2
	15470	Hudson/Zimmer Combi	4.2
	17130	Harris	4.2
	19330	DHS/DCS	4.2
	18190	Stryker Triathlon*	2.3
	17930	Aesculap Taragon TX	4.2

All final drive adaptors are fully compatible with the 700 Series orthodrive® range of products.





Ask for catalogue No. 302 for full details of the De Soutter Medical range of pulse lavage equipment.

Type P30-700 Series

RADIOLUCENT DRILL



Uses D56 type drill bits

Ask for Stericut® catalogue for range of sterile packed saw blades, drill bits, rotary burs and K wires.



n



shown with aseptic batteries.

The BC-700 Battery Charger requires minimal user input, simply insert battery and the BC-700 will charge, recover and recondition it to its optimum state. The large touch-screen display with intuitive menu navigation, displays instant battery charge status and condition. Includes a multi-lingual display and other user settings.

The BC-700 also offers a unique healthcheck facility, profiling the condition of an individual battery, automatically reconditioning it, to provide optimal capacity. Alternatively, a manual healthcheck can be easily selected. The BC-700 Battery Charger accepts all De Soutter Medical batteries, ensuring total backwards compatibility.



BC-700 MULTI BAY CHARGER AND MODULE OPTIONS

Charger - Order code	Charger module description	Charger module - Order code	For battery type	Mains power cordsets - 3 metres long.	ada
15700	Without charger module fitted	-	-	Please specify - Order co	8290
16230	With 4-off CA-703 charger modules	18120	AB-703/AB-704	Euro US/Canada Australia/New Zealand Swiss	8300 8310 8320
16220	With 4-off CA-700 charger modules	15750	SB-703/SB-704		14700

The BC-700 charger modules can be quickly and easily changed to suit the batteries being charged.



SINGLE BAY CHARGERS

Model	Battery type - Order code	For battery type
BC-706	17990	SB-703/SB-704
BC-707	18000	AB-703
BC-708	18010	AB-704

LITHIUM ION STERILE BATTERIES

Why choose Lithium Ion battery technology

De Soutter Medical Lithium Ion batteries offer the surgical team and sterile services a number of tangible benefits over conventional battery technology.

Key advantages are:

- Li-lon technology improves battery 'capacity to weight' ratio by around 22% when compared to equivalent NiMH or NiCad chemistries.
- Significantly extends the useable run time of the power tool
- Eliminates 'memory effect' normally associated with other battery types.
- De Soutter Medical sterile Li-Ion technology readily withstands repeated machine washing and autoclaving.
- Unique fuel gauge incorporated within De Soutter Medical Li-Ion batteries allows the surgical team to instantly assess the battery capacity both before and during use.



LITHIUM ION STERILE BATTERIES

	Model	Description	Order code	Voltage	Capacity mAh
P	SB-703	Small battery	17210	13.2V	1100
	SB-704	Large battery	17220	13.2V	2500





SMALL BATTERY

LITHIUM ION ASEPTIC BATTERIES



OTINCEE BACTIE				
	Battery pack	Aseptic housing	6	Aseptic shield
Model	Description	Order code	Voltage	Capacity mAh
AB-703	Battery pack	17910	10,95V	2000
AH-703	Battery housing	18080	-	-
AS-703	Battery shield	18100	-	-
LARGE BATTE	ERY			
	Battery pack	Aseptic housing	C	Aseptic shield
Model	Description	Order code	Voltage	Capacity mAh
AB-704	Battery pack	17920	14,6V	2000
AH-704	Battery housing	18090	-	-
AS-704	Battery shield	18110	-	-

Loading an aseptic battery pack



Press both catches to open housing



With the aseptic housing open, the sterile operator fits the aseptic shield over the opening



The non-sterile operator inserts the fully charged aseptic battery into the housing.



The non-sterile operator removes the aseptic shield.



The sterile operator closes the aseptic housing until the lid clicks shut, ensuring the housing is fully closed.

CORDED DIRECT POWER



New slim line design. Requires no set-up. Simply connect to the CM-700 Corded Module for instant use.

Mains power cordsets -3 metres long. Please specify - Order code

 UK
 8290

 Euro
 8300

 US/Canada
 8310

 Australia/New Zealand
 8320

 Swiss
 14700







STERILISATION INSERT TRAYS

The introduction of a high performance hard anodising technology onto our handpieces has provided:

- Excellent corrosion resistance and protection against highly alkaline detergents. Durability and long term reliability is significantly improved.
- Ultra tough and exceptionally scratch resistant.

	ASEPTIC BATTERY STERILISATION SYSTEM			
	Set up - optional tray contents	Container and insert tray Order code	Insert tray Order code	
	SINGLE HANDPIECE 1 handpiece, 8 attachments, 8 adaptors, and 1 aseptic battery housing and shield.	18130	17900	
A States	1 handpiece, 6 attachments, 5 adaptors, 3 bur attachments and 2 aseptic battery housing and shields.	20030	20020	
	TWO HANDPIECE			
A CARACTER COR	2 handpieces, 6 attachments, 8 adaptors and 2 aseptic battery housings and shields.	19120	19020	
	1 pistol grip & 1 straight case handpieces, 6 attachments, 8 adaptors and 2 aseptic battery housings and shields.	20390	20350	
	HALF SIZE			
	1 handpiece, 4 attachments, 1 aseptic battery housing and shield.	19400	19290	

STERILE BATTERY STERILISATION SYSTEM





1 handpiece, 8 attachments, 8 adaptors and 1 sterile battery.	17830	17550
2 handpieces, 6 attachments, 8 adaptors and 2 sterile batteries	19160	19060
1 pistol grip & 1 straight case handpieces, 6 attachments, 8 adaptors and 2 sterile batteries.	20400	20340
BATTERY STERILISATION		
2 SB-70X batteries	17390	17400

STERILISATION CONTAINERS

WIRE CONTAINERS



Standard wire container Order code 19010 Accepts standard insert tray

Half size wire container Order code 19000 Accepts half size insert tray

STERILE FILTERED CONTAINERS



UNITED KINGDOM (INTERNATIONAL HEAD OFFICE)

De Soutter Medical Limited Halton Brook Business Park, Weston Road, Aston Clinton, Aylesbury, Bucks HP22 5WF Tel: +44 (0) 1296 634 000 Fax: +44 (0) 1296 634 033 Email: info@de-soutter.com

AUSTRALIA

De Soutter Medical Australia Pty Ltd 2/12-14 Apollo Drive, Hallam Victoria 3803 Tel: +61 (0) 3 9702 4441 Fax: +61 (0) 3 9702 4484 Email: australia@de-soutter.com

AUSTRIA

De Soutter Medical Austria Zweigniederlassung Österreich Dietrichsteingasse 10, A-3400 Klosterneuburg Tel: +43 (0) 676 96 71 770 Fax: +43 (0) 2243 21 656 Email: austria@de-soutter.com

BELGIUM

De Soutter Medical Belgium Bessemerstraat 14 3620 Lanaken Tel: +32 (0) 89/47 15 37 Fax: +32 (0) 89/70 12 19 Email: belgium@de-soutter.com

FRANCE

De Soutter Medical France 1 252 Avenue du Parc des Expositions 33260 La Teste de Buch Tel: +33 (0) 5 56 54 89 36 Fax: +33 (0) 9 70 61 37 60 Email: france@de-soutter.com GERMANY De Soutter Medical Deutschland Bahnhofstraße 4 D-66625 Nohfelden Tel: +49 (0) 68 52-99 12 46 Fax: +49 (0) 68 52-99 12 47 Email: deutschland@de-soutter.com

ITALY

De Soutter Medical Italia Località Fornace SNC 27022 Casorate Primo - PV Tel: +39 (0) 2 9009 4098 Fax: +39 (0) 2 9009 2673 Email: italy@de-soutter.com

NETHERLANDS

De Soutter Medical Nederland Gelderlandhaven 2X 3433 PG Nieuwegein Tel: +31 (0) 85 0491480 Fax: +31 (0) 85 0491489 Email: nederland@de-soutter.com

UNITED STATES OF AMERICA

De Soutter Medical USA, Inc. 224 Rolling Hill Road, Suite 12A Mooresville, NC 28117 Tel: +1 (704) 655 9040 Fax: +1 (704) 987 2035 Email: usa@de-soutter.com



For further information on De Soutter Medical powered instruments and cast saw systems please contact the address in your area.